



Wet System Ultrasafe flat mop

Microfibre and polypropylene flat mop with polyester support for R10/11 non-slip surfaces



Technical information

code	notes	cm (comm. sizes)	cm (real sizes)	C	pcs	kg	m ³
0000H210R		↕ 40 ↘ 14	↕ 40 ↘ 13		25	2,69	0,019
0000H210B		↕ 40 ↘ 14	↕ 40 ↘ 13		25	2,69	0,019

SYSTEM

Flat mop system with flaps, to be used with roll, jaw or flat wringer
Ideal for washing of non-slip or porous surfaces, suitable to remove ingrained dirt

GREEN BOX



EU Ecolabel Certificate



DECITEX of the fibres
Microfibre: 0,16 DTX - Polypropylene: 37,03 DTX



Efficient: microfibre requires less chemical to remove dirt and bacteria, reducing water and chemical consumption

Advantages

- **Time-saving:** thanks to the large cleaning surface and the possibility of reaching corners and cleaning under furniture
- **Ergonomic:** lightweight, it reduces operator's strain
- **Effective:** the abrasive action of polypropylene removes easily dirt
- **Highest hygiene:** microfibre penetrates into the microporosity of the floor, collecting dirt and more than 95% of bacteria
- **Very low friction:** glides effortlessly on non-slip surfaces



Material

Yarn: 50% polypropylene, 40% polyester, 10% polyamide - Support: polyester

Warnings

Use alkaline detergents with a pH below 11

Washing conditions

Guidelines for proper fibre maintenance

Follow the washing instructions (temperatures and dosage) on the detergent packaging
Perform a pre-wash in cold water to remove any residual product used during cleaning operations
Do not use fabric softener
It is recommended to use the convenient laundry nets in washing machine in order to preserve the fibres
Recommended use of normal textile detergent
Do not use detergents with Ph > 11

Specific mop instructions



Washing temperature max 90° C, recommended 60°




Bleaching only with oxygen, do not use chlorine or bleach



Tumble dry or in a dryer possible with low program

Related products



Wet System Light frame



Telescopic handle



Action Pro Dry



Dry wringer